


## Circular Cutter

Application for circular cutting holes by WAS cutting



**Option:  
 Universal Fixing Module  
 for Circular Cutter**



EOD / IEDD

## Circular Cutter

Working area	diameter 0-250 mm (0-9.84 inch)
Controls	axis selection, direction selection, speed control
Material	aluminium
Traversing speed	10-400 mm (0.39-15.75 inch)/min
Space requirement (Ø x H)	730 mm x 560 mm (28.74 x 22.05 inch)
Drive	brushless DC motor
Weight	10 kg (22.05 lb)
Size transportation and storage case (L x W x H)	825 x 520 x 290 mm (32.48 x 20.47 x 11.42 inch)

## Control panel

Electric Power	24 V, 3300 mAh, 2 battery packs
Cable length	15 m (49.21 ft) other lengths on request, up to 200 m (656.17 ft)
Weight	5 kg (11.02 lb)
Size transportation and storage case (L x W x H)	340 x 295 x 150 mm (13.39 x 11.61 x 5.91 inch)

## Universal Fixing Module for Circular Cutter

Working area	diameter 250-800 mm (9.84-31.5 inch)
Material	aluminium
Space requirement (Ø x H)	1400 mm x 750 mm (55.12 x 29.53 inch)
Vacuum pump	230 V AC / 270 W suction performance 75 l (19.81 US gallon)/sec
Suction force per foot base plate	up to 500 N
Weight	10 kg (22.05 lb) (+ 6.5 kg (14.33 lb) vacuum pump)
Vacuum hose length	2 x 25 m (82.02 ft) (other lengths on request)
Size transportation and storage case (L x W x H)	825 x 520 x 290 mm (32.48 x 20.47 x 11.42 inch)