

Circular Cutter



Application for circular cutting holes by the WAS cutting technology.

www.ant-ag.com



GENERAL INFORMATION

Working area	diameter 0-250 mm (0 - 9.84 inch)
Controls	axis selection, direction selection, speed control
Weight	10 kg (22.05 lb)
Space requirement	730 mm x 560 mm (28.74 x 22.05 inch)
Drive	brushless DC motor
Water tank	25 l (6.61 US gallon) netto
Size transportation case	825 x 520 x 290 mm (32.48 x 20.47 x 11.42 inch)



CONTROL PANEL

Electric power	24 V, 3300 mAh, 2 battery packs
Cable length	15 m (49.21 ft) up to 200 m (656.17 ft)
Weight	5 kg (11.02 lb)
Size transportation case (L x W x H)	340 x 295 x 150 mm (13.39 x 11.61 x 5.91 inch)



UNIVERSAL FIXING MODULE FOR CIRCULAR CUTTER

Working area	diameter 250-800 mm (9.84 - 31.5 inch)
Material	aluminium
Space requirement	1/2" quick-release-coupling, max. 6 bar
Vacuum pump	230 V AC / 270 W suction performance 75 l (19.81 US gallon)/ sec
Suction force per foot base plate	up to 500 N
Weight	10 kg (22.05 lb) (+ 6.5 kg (14.33 lb) vacuum pump)
Vacuum hose length	2 x 25 m (82.02 ft) (other lengths on request)
Size transportation case (L x W x H)	825 x 520 x 290 mm (32.48 x 20.47 x 11.42 inch)